

# SMART NATION TRANSLATIONAL LAB

## Intelligent Edge Analytics for Noise Sensing

### Existing Urban Noise Monitoring


- Based on Sound Pressure Level (SPL), insufficient information on what type of noise
- Provides no history tracking of incidents, not helping in creating policy for mitigation
- Class 1 SPL meter is used: high cost
- No remote alert monitoring capability
- No functional upgrade capability, once installed, this only measures SPL

### How It Works

- Environmental sound picked up by MEMS microphones
- Edge analytics for environmental sound
  - Multiclass classification
  - Real-time inference
  - Directional sensing of environmental sound
  - Robust to background noise
- Web application to show types of sound continuously
  - Further visualization of sound statistics

### Audio Intelligent Monitoring at the Edge (AIME)

- Provides holistic monitoring of noise (SPL/noise class/noise duration/DoA)
- Deployed as POC initiative in different areas in Singapore
- Provides 24/7 monitoring with end-to-end capability from sensing up to visualization
- Upgrade possibilities even for deployed sensors, for different sound class / remote alert system
- Using edge computed solution, deep learning and cloud technology for low cost, ease upgradability and flexibility



### Machine Learning Performance

		Predicted														
		A	C	E/R	M	S/S	R	B	C	CH	Alm	G	O/TH	Con	C/C	Exp
Actual	Ambient	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Constr.	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Eng.Rev	20	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Music	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Shout/Scr	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Rain	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Birds	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	CarHorn	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Alarm	8	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	GlassBreak	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Obj.Thrown	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Congregation	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	CarCrash	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Explosion	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0

(a) Version 3.8 model on val. set.

(a) Version 3.8 model on val. set

Figure 1: Model predictions Version 3.8 results

### Hardware Specifications

Weight	750 gram
Dimensions (W x H x D)	135 x 185 x 85mm (without mic)
IP Rating	IP66
Input Power	90 to 264V AC
Microphone	7ch array mic (UMA-8)
Power consumption	5W (optional solar powered)
Data Interface	Built-in Ethernet (*LTE GSM)
Direction-of-arrival	Single source (20 deg acc)

### Deployment Prototype (with Directional of Arrival)



**Acknowledgment:** This work is funded under the Translational R&D Grant Initiative (TRANS Grant), which taps on the research community to solve public sector challenges with innovative use of digital technology. This funding initiative is in support of Singapore's Smart Nation and Digital Government drive, and is jointly managed by the Government Technology Agency of Singapore (GovTech) and the National Research Foundation (NRF).

#### Managing Agencies of TRANS Grant



#### TRANS Lab Partners



#### Project Members

NTU: Prof GAN Woon Seng, Mr. Sim Peng LIM, Mr. Furi Andi KARNAPI, Dr. Joseph TAN, Mr. Linus NG  
MND/MSO: Mohamed HARDI, Adrian EUGovTech: QUEK Yang Boon, Steven TEO, ONG Lay Teen